



DOKIO 110W Mono



NEW! 25-YEAR LINEAR
PERFORMANCE GUARANTEE
AND 5-YEAR EXTENDED
PRODUCT WARRANTY*

Length	740 mm
Width	560 mm
Height	5 mm
Weight	2.7 kg
Frame	Aluminum



FFSP 110W Flexible Foldable Mono Panel

World-class quality

DOKIO products are made by A grade raw materials, and all model have pass through TUV CE ISO Certification!

25-year Linear Performance Guarantee

DOKIO guarantees, over 25 years, that the modules' performance will not decrease by more than 0.7% per year – a distinct added value compared to the two-tiered guarantees usual in the industry.

according to the DOKIO service certificate valid at the time of purchase

www.Dokiosolar.com



FFSP 110W Flexible Foldable Mono Panel

PERFORMANCE UNDER STANDARD TEST CONDITIONS(STC*)

FFSP-110M		
Maximum power	P _{max}	110W _p
Open circuit voltage	V _{oc}	22.5V
Maximum power point voltage	V _{mpp}	18V
Short-circuit current	I _{sc}	6.36 A
Maximum power point current	I _{mpp}	6.11 A

PERFORMANCE AT 1000 W/ M² , NOCT, AM 1.5

Minor reduction in efficiency under partial load conditions at 25° C: at 250 W/m², 95% (+/-3%) of the STC efficiency (1000 W/m²) is achieved.

COMPONENT MATERIALS

Cells per module	36
Cell type	Monocrystalline Silicon
Cell dimensions	156 mm x 52 mm
Front	tempered glass (EN12150)

SYSTEM INTEGRATION PARAMETERS

Maximum system voltage SC II	1000 V
Maximum system voltage USA NEC	600 V
Maximum reverse current	16 A
Increased snowload acc. to IEC 61215	5.4 kN/m ²

THERMAL CHARACTERISTICS

NOCT	47 ° C
TC I _{sc}	0.042 %/° C
TC V _{oc}	-0.33 %/° C
TC P _{mpp}	-0.45 %/° C

ADDITIONAL DATA

PTC rating	90 W
Junction box	IP65
Connector	MC4
Cell efficiency	17.0%
DOKIO Plus-Sorting*	P _{Flash} ≥ P _{max}
Power tolerance*	+/- 3 %

*Only modules with flash-tested power ≥ P_{max} are delivered.
Linear warranty guarantees Year 1 module output to ≥ 97% of P_{max}

